

Commissioner for Patents  
Amendment dated November 15, 2004  
Response to Office Action dated August 13, 2004  
Page 3 of 9

Serial: 10/057643  
Art Unit: 2114  
Examiner: Matthew  
Docket No. RPS9 2001 0149 US1

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

### Listing of Claims:

1 (original). A data processing system, comprising:

at least one main processor connected to a system bus;

a system memory connected to the system bus and accessible to each of the main processors;

a tamper mechanism configured to change state responsive to insertion of the system into a slot in a rack enclosure; and

a local service processor, connected to the tamper mechanism and configured to update an insertion log responsive to detecting a changed state of the tamper mechanism, wherein the insertion log provides a history of at least some rack insertions to which the system has been subjected.

2 (original). The system of claim 1, further comprising a non-volatile storage element accessible exclusively to the local service processor and containing the insertion log.

3 (original). The system of claim 2, wherein the insertion log includes an insertion counter, and wherein the local service processor is configured to increment the insertion counter upon each insertion.

4 (original). The system of claim 3, wherein the local service processor is configured to issue an alert responsive to the insertion counter exceeding a predetermined value.

5 (original). The system of claim 1, further comprising a battery backed real-time clock connected to the local service processor, wherein the local service processor is configured to include real-time information corresponding to each insertion event in the insertion log.

6 (original). The system of claim 1, wherein each entry in the insertion log includes the identity of the rack enclosure and the geographical address of the slot of the corresponding insertion event.

7 (currently amended). The system of claim 1, wherein the local service processor is configured to detect the tamper mechanism state and update the insertion log responsive to a power event such that the insertion log update is independent of configuring the data processing system with a boot image.

**BEST AVAILABLE COPY**

Commissioner for Patents  
Amendment dated November 15, 2004  
Response to Office Action dated August 13, 2004  
Page 4 of 9

Serial: 10/057643  
Art Unit: 2114  
Examiner: Matthew  
Docket No. RPS9 2001 0149 US1

8 (original). A data processing network, comprising:

a plurality of server blades connected to a common network, each blade comprising at least one main processor connected to a system bus, a system memory connected to the system bus and accessible to each of the main processors, a tamper mechanism configured to change state responsive to insertion of the system into a slot in a rack enclosure; and a local service processor, connected to the tamper mechanism and configured to update an insertion log responsive to detecting a changed state of the tamper mechanism, wherein the insertion log provides a history of at least some rack insertions to which the system has been subjected.

9 (original). The network of claim 8, further comprising a non-volatile storage element accessible exclusively to the local service processor and containing the insertion log.

10 (original). The network of claim 9, wherein the insertion log includes an insertion counter, and wherein the local service processor is configured to increment the insertion counter upon each insertion.

11 (original). The network of claim 10, wherein the local service processor is configured to issue an alert responsive to the insertion counter exceeding a predetermined value.

12 (original). The network of claim 8, further comprising a battery backed real-time clock connected to the local service processor, wherein the local service processor is configured to include real-time information corresponding to each insertion event in the insertion log.

13 (original). The network of claim 8, wherein each entry in the insertion log includes the identity of the rack enclosure and the geographical address of the slot of the corresponding insertion event.

14 (currently amended). The network of claim 8, wherein the local service processor is configured to detect the tamper mechanism state and update the insertion log responsive to a power event such that the insertion log update is independent of configuring the data processing system with a boot image.

15 (original). A computer program product comprising a set of computer executable instructions for logging server blade insertions in a data processing network, the instructions being stored on a computer readable medium, comprising:

computer code means for determining the state of a tamper latch of the server blade; and

computer code means, responsive to detecting a tamper latch state change, for updating an insertion log wherein the insertion log is local to the server blade and provides a history of at least some rack insertions to which the system has been subjected.

Commissioner for Patents  
Amendment dated November 15, 2004  
Response to Office Action dated August 13, 2004  
Page 5 of 9

Serial: 10/057643  
Art Unit: 2114  
Examiner: Matthew  
Docket No. RPS9 2001 0149 US1

16 (original). The computer program product of claim 15, wherein the insertion log comprises at least a portion of a non-volatile storage element accessible exclusively to the local service processor.

17 (original). The computer program product of claim 16, wherein the insertion log includes an insertion counter, and wherein the computer program product is configured to increment the insertion counter upon each insertion.

18 (original). The computer program product of claim 17, wherein the code means is configured to issue an alert responsive to the insertion counter exceeding a predetermined value.

19 (original). The computer program product of claim 15, wherein each entry in the insertion log includes the identity of the rack enclosure and the geographical address of the slot of the corresponding insertion event.

20 (currently amended). The computer program product of claim 15, wherein the local service processor is configured to detect the tamper mechanism state and update the insertion log responsive to a power event such that the insertion log update is independent of configuring the data processing system with a boot image.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKewed/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: \_\_\_\_\_**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**